

Subject to change. For projects with specs outside these listed standards please call 1-800-538-8377 or email signage@geminimade.com for additional consultation.



Finish: Hairline, Polished or Painted

Height	1.5" Depth Min. Stroke	2" Depth Min. Stroke	2.5" Depth Min. Stroke	3" Depth Min. Stroke	
Punctuation	1.0"	1.0"	1.0"	1.0"	Block & Upper Case Only
2.5"	0.6"	0.6"	NA	NA	Block & Upper Case Only
3.0"	0.6"	0.6"	NA	NA	Block Only
4.0"	0.6"	0.6"	NA	NA	Block Only
5.0"	0.6"	0.6"	NA	NA	Block or Squared Serif
6.0"	0.6"	0.6"	NA	NA	Block or Squared Serif
7.0"	0.6"	0.6"	NA	NA	Block or Squared Serif
8.0"	1.0"	1.0"	0.65"	0.65"	Block or Squared Serif
9.0"	1.0"	1.0"	0.65"	0.65"	Block or Squared Serif
10.0"	1.0"	1.0"	0.65"	0.65"	Block or Squared Serif
11.0"	1.0"	1.0"	0.65"	0.65"	Block or Squared Serif
12.0"	1.0"	1.0"	0.65"	0.65"	Block or Squared Serif

LED

Wire hole .25"

Standard LED

Module .38" x .622"

Strip .25" wide

RGB LED NA


Cable 10' Long Standard

Stud Placement



Studs placed at least .7" away from top and bottom of letter.

Minimum Opening



.3" All Gauges

Openings/gaps must be at least this large to produce.

Material Gauge

Face 16g (.047)

Return 24g (.023)

Miscellaneous

No Script fonts

Stud mount use 6-32